

HG1360NM2

Non-marking, Cup Heel Grounder

Description

Non-marking heel grounders help keep your controlled environment clean. The HG1360NM2 is constructed from a non-marking and highly dissipative three layer rubber. The reversible 1.5" wide rubber cup, secures both at the back and underneath the heel. Its 7.5" length rubber provides enough cup volume to fit comfortably on those with larger shoe sizes. The 7" stretch hook and loop enclosure ensures a comfort fit.

These heel grounders connect the person wearing them to ground via a proper floor mat or flooring material. Wearing the conductive ribbon inside the shoe or sock assures proper electrical contact with the user. A buried 1 meg ohm resistor is standard. Heel grounders are worn on both feet to provide consistent grounding while in motion.



Key Features: • Non-marking Rubber • Buried resistor • 1.5" cup design

Product Specifications

Resistor:	1 meg ohm (+/- 5% tolerance), buried
Color:	Blue hook and loop, Elastic, grey non-marking rubber
Sole Interior:	Non-Marking Rubber
Sole Exterior:	Conductive Rubber 5x10^3
RTG(1 Meg):	<10 meg
Cup Design	1.5" wide, x 7.3" Three Layer Rubber
Charge Decay:	<0.01Sec
Ribbon:	Conductive nylon

Product Number

<u>Item Number</u>	<u>Description</u>
HG1360NM2	Heel Grounder, non-marking, 1 meg

Note: Heel grounders are dependent on foot perspiration in the shoe to create and maintain electrical contact with the body. The HG1360NM2 works reliably with stockings and socks due to the moisture present.

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.



Transforming Technologies, LLC

3719 King Road.
Toledo, OH 43617

Phone: 1.419.841.9552
Fax: 1.419.841.3241

www.transforming-technologies.com

Outstanding Alternatives in Static Control