

ESD Warning Labels

Applications:

ESD Labels are used to signify static sensitive items are present and ESD precautions should be taken

Specifications:

LABELS PER ROLL: 500
 BACKING: PAPER
 THICKNESS: 3.8 MIL
 OPACITY: 88.5%
 BRIGHTNESS: 90%
 BASIS WEIGHT: 54 LBS./ REAM
 TENSILE: 26 LBS./IN.
 ADHESIVE: PERMANENT LATEX
 TEMPERATURE:

Application (Minimum): -20° F

Performance: -65° to 180° F

PAPER: 54# Semigloss White Litho



LB9010 5/8 x 2



LB9020 3/8 x 1-1/4



LB9030 5/8 x 2



LB9040 5/8 x 2



LB9050 5/8 x 2



LB9060 1 x 2-1/2



LB9070 1-3/4 x 3



LB9120 1-3/4 x 2-1/2
 LB9110 1 x 1-1/2



LB9180 1-3/4 x 2-1/2



JEDC-14/Symbol
 LB9140 1-3/4 x 2-1/2
 LB9130 1x1-1/2



JEDC-14/Symbol
 - Removable -
 LB9140 1-3/4 x 2-1/2
 LB9130 1x1-1/2



JEDC-14/Symbol
 LB9120 1-3/4 x 2-1/2
 LB9110 1x1-1/2



LB9090 2X2



LB9081 4 x 4
 LB9080 2 x 2
 Removable Labels Available



LB9160 3-1/2 x 3



MIL STD 129N/Symbol
 LB9083 4 x 4
 LB9082 2 x 2
 Removable Labels Available



LB9201 3x5
 LB9191 1-1/2 x 3

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.