TRANSFORMING TECHNOLOGIES

OUTSTANDING ALTERNATIVES IN STATIC CONTROL

Apparel

Rev: 2023-03-17

GL9100 Series ESD Hot Gloves

Specifications:

White

Small

Large

Medium

Extra Large

14" Length

Color:

Length:

Electrical: Tribocharging:

GL9101:

GL9102:

GL9103:

GL9104:

Face Fabric: Inner Liner:

Temperature:

Part Numbers:

Have static control and heat protection in one cleanroom compatible glove.

Designed for printed circuit boards, hybrid circuits, semiconductors and other processes, the GL9100 series ESD safe hot glove provides static protection without compromising cleanliness. Gloves resist heat up to 302°F or 150°C.

These gloves use a polyester knit fabric suffused with carbon fiber. Heat protection is enhanced with a 100% inner tricot knit polyester fabric liner and a full 14 inch length. A cuff mounted grounding snap is also included.

Meets or exceeds requirements of ANSI ESD-S20.20 and the recommendations of ESD 4.1.

Polyester knit fabric suffused with carbon fiber.

100% inner tricot knit polyester fabric.

Typical results less than 300 volts

Resist up to 302°F (150°C) RTT < 1 x 10^10 Ohms/Sq.



Features

- Have Static Control and Heat Resistance In the Same Glove
- Gloves resist up to 302°F(150°C)
- Cuff Mounted 4mm Grounding Snap
- 100% inner tricot knit polyester fabric
- Cleanroom Safe

GL9100 Series Glove Measurements*

Size	S	М	L	XL
Length (in)	13.5	13.5	14	14
Width (in)	5	6	6	6.5
Weight (oz)	1.2	1.5	1.8	1.9
Cuff Color	Green	Red	Yellow	Blue

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.

www.transforming-technologies.com