

TTCRB Series

Conductive Rubber Bands

Description

Conductive rubber bands are specially manufactured to handle the problem of static in the semiconductor and electronics industry. Conductive rubber bands are used to bundle and protect ESD sensitive IC tubes, trays, boxes and carriers quickly and safely.

- Vulcanized Natural Rubber
- Surface Resistivity: 10^6 ohms/sq
- Static Decay Rate: Less than 2 sec
- Permanently ESD, Washable and Reusable



Product Specifications

- Surface Resistivity 10^6 Ohms/sq.
- Surface Decay Less than 2 secs.
- Lead <2.26 PPM
- Cadmium <6.40 PPM
- Mercury <1.08 PPM
- Chromium Hexavalent <0.18 PPM

Product Number

<u>Item Number</u>	<u>Description</u>	<u>Approx. # Per Bag*</u>
TTCRB2	Conductive Rubber Band - 4.75"x1/8"	475
TTCRB3	Conductive Rubber Band - 6.25"x1/8"	300
TTCRB4	Conductive Rubber Band - 4.00"x1/8"	600
TTCRB5	Conductive Rubber Band - 4.00"x1/4"	300
TTCRB10	Conductive Rubber Band - 4.5"x1/2"	175

*Minimum order of 4 bags

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.



Transforming Technologies, LLC

3719 King Road.
Toledo, OH 43617

Phone: 1.419.841.9552
Fax: 1.419.841.3241

www.transforming-technologies.com

Outstanding Alternatives in Static Control